

**IN THE SPECIFICATION**

Please replace the paragraph from page 4 line 27 to page 5 line 9 with the following amended paragraph:

(6) Here, in above (4) and (5), the lighting control unit may include reception judgement judgment unit for judging whether the contents information is received within a predetermined period of time since the request detecting unit detects that the request has been made, and in the case where the reception judgement judgment unit may judge that the contents information is not received within the predetermined period of time, the lighting control unit displays on the display panel a message that the contents information failed to be received and turns on the backlight.

Please replace the paragraph on page 5 ll. 10-25 with the following amended paragraph:

(7) In above (2), the display procedure may display all of the received contents information on the display panel, the request detecting unit may include an instruction accepting unit for accepting from the user an instruction for requesting the contents information and detect that the request has been made by detecting the instruction, and the lighting control unit may include reception judgement judgment unit for judging whether the contents information is received within a predetermined period of time since the request detecting unit detects that the request has been made, and in the case where the reception judgement judgment unit may judge that the contents information is not received within the predetermined period of time, the lighting control unit displays on the display panel a message that the contents information failed to be received and turns on the backlight.

Please replace the paragraph from page 5 line 26 to page 6 line 15 with the following amended paragraph:

(8) Alternatively, in above (2), the display procedure may display all of the received contents information on the display panel, the request detecting unit may include an instruction accepting unit for accepting from the user an instruction for requesting the contents information and detect that the request has been made by detecting transmission of the instruction, and the lighting control unit may include reception ~~judgement~~ judgment unit for judging whether the contents information is received within a predetermined period of time since the request detecting unit detects that the request has been made, and in the case where the reception ~~judgement~~ judgment unit may judge that the contents information is not received within the predetermined period of time, the lighting control unit displays on the display panel a message that the contents information failed to be received and turns on the backlight.

Please replace the paragraph on page 10 ll. 8-14 with the following amended paragraph:

Reception error information is data for displaying the reception error message. The reception error information is read out and reproduced by the control unit 5, and then output to the display unit 6. For example, with this information, a ~~massage~~ message “Requested information failed to be received from the server. Please retry it after a while.” is displayed on the display.